


# SET-D4TP100-MC

## Area / Local BUS Cable



Recommended cable for connecting the LCM's or DDC's together (Area and Local BUS Networks):-


Connection of:  
 SET-DDC  
 SET-DLCM  
 SET-DAC  
 SET-DFP

### Key Features

- » 4-Core comprising of two twisted pairs of stranded tinned copper (7 x 0.3 mm<sup>2</sup> per core)
- » Each pair individually foil shielded 300V RMS.
- » Inner shield drain wire stranded tinned copper (7 x 0.2 mm<sup>2</sup>)
- » Core colour code- Pair #1 = Red & Black.  
Pair #2 = Green & White.
- » Grey LSHF (Low Smoke Halogen Free) outer sheath.
- » Overall nominal diameter- 5.0 mm.
- » Mains containment rated, suitable to run alongside 600V.
- » For use with RS485 data networking.
- » 100m reel.
- » Mode Lighting products are guaranteed for two years.



## System Architecture



## Technical Data

Output Cable					
Type	» 3, 4, 5 or 6 core cable				
Supply Plug	» Weiland GST18i6 (Black and Blue)				
CSA per core	» 1.5mm <sup>2</sup>				
Core Material	» Copper				
Sheathing					
Rating	» LSHF Low Smoke Halogen Free				
Colour Coding					
Red	» Dimming +				
White	» Dimming -				
Black	» Emergency Live				
Blue	» Neutral				
Green	» Earth				
Brown	» Live				
Part Codes					
Cores	3 Metre	4 Metre	5 Metre	7 Metre	Description
3 Core	SET-OP-3C-3M	SET-OP-3C-4M	SET-OP-3C-5M	SET-OP-3C-7M	Mains Output Lead for Switching
4 Core	SET-OP-4C-3M	SET-OP-4C-4M	SET-OP-4C-5M	SET-OP-4C-7M	Mains Output Lead for Switching and Maintained Live
5 Core	SET-OP-5C-3M	SET-OP-5C-4M	SET-OP-5C-5M	SET-OP-5C-7M	Output Lead with Dimming
6 Core	SET-OP-6C-3M	SET-OP-6C-4M	SET-OP-6C-5M	SET-OP-6C-7M	Output Lead with Dimming and Maintained Live
6 Core Extension	SET-OP-6C-3M-EXT	SET-OP-6C-4M-EXT	SET-OP-6C-5M-EXT	SET-OP-6C-7M	Output Lead with Dimming and Maintained Live

## Works With

Product Codes	Description
SET-DLCM3	» Pluggable Lighting Control Module
SET-DLCM5	» Pluggable Lighting Control Module



Mode Lighting Limited. The Maltings, 63 High Street, Ware, Hertfordshire, SG12 9AD. United Kingdom.  
 Tel: +44 (0) 1920 462121 | Fax: +44 (0) 1920 466881 | Email: sales@modellighting.com | www.modellighting.com