

SET-OP Luminaire Lead

set square
energy saving controls




The SET-OP range of output leads connects the light fitting to the DLCM (Lighting Control Module). A multicore cable with colour coded cores of 1.0mm² stranded copper.

Key Features

- » Output Lead for connecting DLCM to Light Fitting.
- » Low Smoke Halogen Free (LSHF) sheathing.
- » Carries Mains Power, Dimming Pair and Maintained Emergency Live.
- » Mode Lighting products are guaranteed for two years.



System Architecture



Technical Data

Output Cable					
Type	» 3, 4, 5 or 6 core cable				
Supply Plug	» Weiland GST18i6 (Black and Blue)				
CSA per core	» 1.5mm ²				
Core Material	» Copper				
Sheathing					
Rating	» LSHF Low Smoke Halogen Free				
Colour Coding					
Red	» Dimming +				
White	» Dimming -				
Black	» Emergency Live				
Blue	» Neutral				
Green	» Earth				
Brown	» Live				
Part Codes					
Cores	3 Metre	4 Metre	5 Metre	7 Metre	Description
3 Core	SET-OP-3C-3M	SET-OP-3C-4M	SET-OP-3C-5M	SET-OP-3C-7M	Mains Output Lead for Switching
4 Core	SET-OP-4C-3M	SET-OP-4C-4M	SET-OP-4C-5M	SET-OP-4C-7M	Mains Output Lead for Switching and Maintained Live
5 Core	SET-OP-5C-3M	SET-OP-5C-4M	SET-OP-5C-5M	SET-OP-5C-7M	Output Lead with Dimming
6 Core	SET-OP-6C-3M	SET-OP-6C-4M	SET-OP-6C-5M	SET-OP-6C-7M	Output Lead with Dimming and Maintained Live
6 Core Extension	SET-OP-6C-3M-EXT	SET-OP-6C-4M-EXT	SET-OP-6C-5M-EXT	SET-OP-6C-7M	Output Lead with Dimming and Maintained Live

Works With

Product Codes	Description
SET-DLCM3	» Pluggable Lighting Control Module
SET-DLCM5	» Pluggable Lighting Control Module



Mode Lighting Limited. The Maltings, 63 High Street, Ware, Hertfordshire, SG12 9AD. United Kingdom.
 Tel: +44 (0) 1920 462121 | Fax: +44 (0) 1920 466881 | Email: sales@modelighting.com | www.modelighting.com